

10/1996, 370

EAST - [10796370.wsp:1]

File View Edit Tools Window Help

Icons for file operations

Drafts

Pending

Active

Failed

Saved

S2: (4394) on near9 off

S3: (4394) S2

S4: (4) S1 near9 S2

S1: (47910) port near9 power

S5: (4691) switch\$5 near9 S1

S6: (611) supply\$5 near9 port near9 power near9 S5

S8: (24) program\$4 near9 S7

S7: (1251) port near9 power near9 mode

S9: (33238) power near5 port

S10: (95834) user near9 mode

S11: (10) S9 near9 S10

S12: (156472) select\$5 near9 (port pin)

S13: (4766) nonpower\$3 non-power\$3

S17: (1) on near9 off near9 S9

S20: (1931045) mode same11

S23: (4348) S9 same off same off

S24: (3763553) S9 sameonsame off

S25: (35) S9 same on same off

S14: (5) S12 near9 S13

S15: (89) S13 near9 (port pin)

S16: (1) configur\$4 near9 S9 near9 S10

S18: (90) on near9 off near9 port

S19: (831) power same port same on same off

S21: (35) mode same S19

S22: (5) power near20 port near20 on near20 off

S26: (1) ("5552991").PN.

S28: (47942) port near9 power

S29: (15) S27 with S28

S27: (33999) ring near9 detect\$3

Favorites

Tagged (1)

UDC

Queue

Trash

Search

Ref

Browse

Clear

DBs

US-PGPUB, USPAT, USOCR, FPRS, EPO, JPO, DERWENT, IBM, TDB

☒ Burels

Default operator:

OR

☐ Highlight all hit terms initially

S27 with S28

BRS form S&R form Image Text HTML

	U	Document ID	Issue Date	Pages	Title	Current OR	Current XRef	Retrieval Cla	Inventor	S	C	P	2	3
1	<input type="checkbox"/>	US 2005/081242	2005/04/21	19	Protected bidirectional wiring	398/119			Chen, Manli et al	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Hits Details HTML

Ready

NUM